



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F04B 27/10, 27/18	A2	(11) International Publication Number: WO 00/53927 (43) International Publication Date: 14 September 2000 (14.09.00)
--	----	---

(21) International Application Number: PCT/BE99/00033

(22) International Filing Date: 9 March 1999 (09.03.99)


(71)(72) Applicant and Inventor: HEYLEN, Carlo [BE/BE]; Vlin-
derweg 25, B-2360 Oud-Turnhout (BE).(74) Agents: PIERAERTS, Jacques et al.; Gevers & Vander
Haeghen, Rue de Livourne 7, B-1060 Brussels (BE).

(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: PISTON COMPRESSOR



(57) Abstract

The present invention relates to a piston compressor comprising (a) at least one fixed cylinder (1) which is positioned essentially parallel with respect to a central axle (8), in which cylinder (1) a piston (3) is moveably mounted; (b) a tumble disc (2) with a centre (9) which is located on the central axle (9), which tumble disc (2) is tiltably mounted in all directions; and (c) with respect to the central axle (8), axial, ball bearing component (6) which is rotatably mounted and eccentrically coupled to the tumble disc (2).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Piston compressor.

The present invention relates to a novel piston compressor.

5 The piston compressor of this invention presents the advantage that notwithstanding the presence of a large number of cylinders as compared to the conventional piston compressors, its weight and volume can be significantly reduced. With the present invention, the volume and weight of the piston compressor can be reduced with at least 75%. The piston compressor of this invention presents the
10 additional advantage that it operates almost noise and vibration free.

Because the piston rods execute a displacement which is mainly rectilinear, almost no lateral pressure is exerted to the pistons, thus reducing friction losses and wearing so that almost no friction losses occur.

15 With the piston compressor of the present invention, the compression and flow rate can be adjusted, either individually or simultaneously, either manually, electronically, electrically or computer controlled, without necessitating the use of additional pressure relief valves or the like.

20 The piston compressor of this invention comprises (a) at least one fixed cylinder which is positioned essentially parallel with respect to a central axle, in which cylinder a piston is moveably mounted; (b) a tumble disc with a centre which is located on the central axle, which tumble disc is tiltably mounted in all directions; and a
25 with respect to the central axle 8, axial, ball beared component 6 which is rotatably mounted and excentrically coupled to the tumble disc.

CONFIRMATION COPY

The tumble disc can be moved along the direction of the axle through a worm drive. Depending on the direction in which the tumble disc is displaced, the tumble disc is capable of increasing or decreasing the cylinder volume and controlling the length of stroke of the piston, thus adjusting the compression and flow rate.

The displacement mechanism of the tumble disc comprises a piston which is moveable in a cylinder. One end of the piston is hingedly connected to the piston rod, the other of the piston is hingedly connected to the tumble disc. The displacement mechanism of the tumble disc further comprises an axial ball beared rotatable component which is excentrically connected to the tumble disc.

The invention is further elucidated in the attached figures and description of the figures without being limited thereto.

In figure 1, a cross section of a preferred embodiment of the piston compressor of the present invention is shown.

In figure 2, a circular positioning of the cylinders within the piston rod is shown.

The piston compressor shown in figure 1 comprises at least one, preferably eight cylinders 1 mounted along a circle. The cylinders 1 are preferably mounted in a common cylinder block 7 and mounted along a circle which extends around the central axle 8 of the cylinder block 7.

The embodiment of the piston compressor shown in figure 2 comprises a tumble disc 2 which is rotatable in all directions, under a fixed angle. Each cylinder 1 comprises a piston 3 which is moveable within the cylinder 1. Each piston is connected at one end to the hingedly mounted piston rods through a hingeable ball 13, and at the other end to the tumble disc 2. The piston compressor further comprises a rotatable part 6. The tumble disc 2 is excentrically coupled to the rotatable

- 3 -

part 6. The tumble disc 2 comprises a centre 9. The tumble disc 2 is mounted under a fixed angle with respect to the central axle 8 and is tiltably mounted around its centre 9 on the axle 8. In order to allow a smooth displacement centre 9 is connected through a cardan joint 10 or an equivalent joint.

The rotatable part 6 is axially placed with respect to the central axle 8 and ball beared. The rotatable part 6 and the tumble disc are preferably coupled to each other through meshing parts which are rotatable and moveable with respect to each other along the central normal 14 of the tumble disc 2. Thereto, the tumble disc comprises a protruding axle part 15 that extends along the central normal 14 and fits into a seating 16 in the rounded tip of the rotatable part 6.

The cardan joint 10 or its equivalent, is supported by a support 12 which is slideable within the support block 7. The sliding axes 17 which are fixed to the supporting block 7 allow that the supporting part 12 can be rotated around the central axle 8.

The supporting part 12 has an internal thread 18, which is trapezoid in the embodiment shown in figure 2, but which can be made in all kinds of worm like threads. The worm spindle 19 is fixed by a cover plate 20. At the end of the worm spindle 19, for example a gear wheel 21 can be mounted, which may be driven by a second gear wheel 22 mounted on the axle of a servo motor 23. Gear wheel 21 can be a worm wheel, in which case the gear wheel 22 is replaced by a worm spindle attached to a servo motor 23 or step motor. In stead of a gear wheel 22, use can be made of a handle, so that the worm spindle 19 can be manually, externally rotated.

The servo motor 23 is preferably controlled by a programmed computer, microprocessor or P.L.C. 24, which receives its data from a temperature registration device 25, pressure gauge 26 and a flow meter 27. The servo motor 23 can also be controlled by a control

panel 28. The driving motor for driving the computer also receives data from the computer, microprocessor or P.L.C 24.

The manner in which the compressor functions can be derived from figure 1. In case the axle 30 is driven by the drive motor 29, the protruding axle part 15 will be execute a circular displacement, as a consequence of which the tumble disc 2 will be tilted and the piston executes a reciprocating movement, going up and down. The piston compressor comprises the required inlets 31, inlet valves 32, outlets 33 and outlet valves 34, so as to obtain the compression effect.

According to a preferred embodiment of figure 1, the chambers of the cylinders are filled almost twice. When the piston 3 is moved to the upper dead point, the lower part of the chamber below the piston can be filled through the opening 31. During the downward movement of the piston, an under pressure is created above the piston 3, as a consequence of which valve 32 is opened and the cylinder is filled with gas or air. Thereby, a pressure is created below piston 3 until the piston 3 has reached its lowest dead centre point. At that point, the inlet of channel 36 is opened, so that the compressed gas (for example air) is freed in the cylinder, as a consequence of which this cylinder 1 contains almost the double volume of gas, at only a half stroke. This results in a higher yield of the piston compressor.

In the piston compressor of this invention, the adjustment of the centre 9 of the tumble disc is rather special. By rotating the worm spindle 19, the support 12 is moved forward or backward, depending on the direction in which the worm spindle 19 is rotated. Thereby the volume of the cylinder chamber is increased or decreased. In that way the pressure and flow rate can be adjusted according to the data that have been programmed in the computer, microprocessor of PLC 24, which then start a servo motor 23 for determining the correct position of the support point 9.

When the support 12 is pulled back by the worm spindle 19, which worm spindle 19 is rotated by the servo motor 23, the angle of the axis is varied and the length of the stroke is varied. This is possible through a self aligning bearing 16. In that way the energy consumption can be reduced to a minimum when a low pressure and/or flow rate are required.

The present invention is not limited to the example and drawings described above.

CLAIMS.

1. A piston compressor characterised in that it comprises (a) at least one fixed cylinder (1) which is positioned essentially parallel with respect to a central axle (8), in which cylinder (1) a piston (3) is moveably mounted; (b) a tumble disc (2) with a centre (9) which is located on the central axle (9), which tumble disc (2) is tiltably mounted in all directions; and a with respect to the central axle (8), axial, ball beared component (6) which is rotatably mounted and excentrically coupled to the tumble disc (2).
2. A piston compressor as claimed in claim 1, characterised in that centre (9) of the tumble disc (2) is hingedly mounted within said piston compressor.
3. A piston compressor as claimed in claim 1 or 2, characterised in that the tumble disc (2) is hingedly attached by means of a cardan joint (10).
4. A piston compressor as claimed in any one of claims 1 to 3, characterised in that the piston (3) comprises a piston rod (4), which is hingedly connected to the piston (3) and the tumble disc (2) through a ball joint (5, 13).
5. A piston compressor as claimed in any one of claims 1 to 4, characterised in that the piston (3) comprises a piston rod (4) which is hingedly mounted in the pistons (3) through ball joints (13).
6. A piston compressor as claimed in any one of claims 1 to 5, characterised in that the rotatable part (6) and the tumble disc (2) are coupled to each other through meshing parts which are rotatable and moveable with respect to each other along a normal through the central normal (14) of the tumble disc (2).
7. A piston compressor as claimed in claim 6, characterised in that the meshing parts comprise an axle part (15) of the tumble disc (2), which axle part (15) extends parallel to the normal (14)

and is provided on the tumble disc (2), and a seal for this axle part, which is applied in the rotatable component (6) under an angle.

8. A piston compressor as claimed in claim 7, characterised in that the axle part (15) of the tumble disc (2) is mounted in the bearing (16) of the rotatable component (6) through a ball joint (37).

9. A piston compressor as claimed in any one of claims 1 to 8, characterised in that it comprises a control mechanism comprising a worm shaft (19) and a support (12) positioned by a cover plate (20), whereby the tumble disc (2) is movably mounted at its centre point (9) along the central axle (8), wherein the piston rods (4) are connected to the tumble disc (2) and are moveable together with the tumble disc (2) and the pistons (3) are connected to the piston rods (4) and are moveable together with the piston rods (4).

10. A piston compressor as claimed in claim 6, characterised in that it comprises a built in control mechanism which is driven by a servo motor (23), through gear wheels (21) and (22).

11. A piston compressor as claimed in claim 9 or 10, characterised in that the control mechanism is provided with means for either manually, electrically by means of a switchboard, electronically by a programmed computer, a microprocessor or P.L.C. (24), controlling the control mechanism.

12. A piston compressor as claimed in claim 11, characterised in that it comprises a drive motor (29), the rotational speed of which can be controlled by means of a switch board, a programmed computer, a microprocessor or P.L.C. (24).

13. A piston compressor as claimed in claim 11 or 12, characterised in that the programmed computer, microprocessor or P.L.C. (24) are controlled by a temperature sensor (25), a pressure sensor (26) or a flow rate sensor (27).





Fig. 1

Fig. 2



THIS PAGE BLANK (USPTO)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 September 2000 (14.09.2000)

PCT

(10) International Publication Number
WO 00/53927 A3

(51) International Patent Classification⁷: **F04B 27/10**,
27/18

(21) International Application Number: PCT/BE99/00033

(22) International Filing Date: 9 March 1999 (09.03.1999)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: HEYLEN, Carlo [BE/BE]; Vlinderweg 25,
B-2360 Oud-Turnhout (BE).

(74) Agents: PIERAERTS, Jacques et al.: Gevers & Vander
Haeghen, Rue de Livourne 7, B-1060 Brussels (BE).

model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS,
JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU,
SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR,
TT, UA, UG, US, UZ, VN, YU, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM,
AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT,
BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

(88) Date of publication of the international search report:
2 May 2002

(81) Designated States (*national*): AL, AM, AT, AT (utility
model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU,
CZ, CZ (utility model), DE, DE (utility model), DK, DK
(utility model), EE, EE (utility model), ES, FI, FI (utility

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: PISTON COMPRESSOR



(57) Abstract: The present invention relates to a piston compressor comprising (a) at least one fixed cylinder (1) which is positioned essentially parallel with respect to a central axle (8), in which cylinder (1) a piston (3) is moveably mounted; (b) a tumble disc (2) with a centre (9) which is located on the central axle (9), which tumble disc (2) is tiltable mounted in all directions; and c) with respect to the central axle (8), axial, ball bearing component (6) which is rotatably mounted and eccentrically coupled to the tumble disc (2).

WO 00/53927 A3

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F04B27/10 F04B27/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F04B F01B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 564 953 A (CRESPIN) 16 January 1924 (1924-01-16) figure 4 page 2, line 1-88	1-4,6,9
A	PATENT ABSTRACTS OF JAPAN vol. 007, no. 291 (M-265), 27 December 1983 (1983-12-27) & JP 58 162780 A (TOYODA JIDO SHOKKI SEISAKUSHO KK;OTHERS: 01), 27 September 1983 (1983-09-27) abstract	1,2,4-6, 9-13
A	US 2 457 339 A (BERTEA) 28 December 1948 (1948-12-28) figures 1,2 column 2, line 35 -column 3, line 52 -/-	1,2,6,9

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

4 November 1999

11/11/1999

Name and mailing address of the ISA

European Patent Office, P.O. 5918 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Wassenaar, G

NATIONAL SEARCH REPORT

International Application No. **99/00033**
PCT/BE 99/00033

C. (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2 570 698 A (MANSEAU) 9 October 1951 (1951-10-09) figure 1 column 1, line 1 - line 35	1,2,6,9
A	EP 0 081 205 A (LEHMANN DIETER) 15 June 1983 (1983-06-15) figure 1 abstract	1,2,6,9

INTERNATIONAL SEARCH REPORT

Information on patent family

Internat. Appl.

PCT/BE 99/00033

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 564953	A	16-01-1924	NONE	
JP 58162780	A	27-09-1983	NONE	
US 2457339	A	28-12-1948	NONE	
US 2570698	A	09-10-1951	NONE	
EP 0081205	A	15-06-1983	DE 3148027 A	09-06-1983
			AT 20687 T	15-07-1986
			JP 58107816 A	27-06-1983